

TABLE 11 DESIGN LOAD CALCULATION FOR DN 500mmSS

DATA: Crushing strength = 60 kN/m; Unit weight of backfill = 19.6 kN/m³; Ext. dia. = 581mm
 Ku' = 0.13; Ku = 0.19; r_{sd}p = 0.5; Traffic load = 112.5 kN; Factor of Safety = 1.25

Trench cover m	Design load kN/m	Bedding factor	Design load kN/m	Bedding factor	Design load kN/m	Bedding factor	Design load kN/m	Bedding factor
0.6	79.51	1.66	79.51	1.66	79.51	1.66	79.51	1.66
0.7	71.34	1.49	71.34	1.49	71.34	1.49	71.34	1.49
0.8	66.07	1.38	66.07	1.38	66.07	1.38	66.07	1.38
0.9	50.64	1.06	50.64	1.06	50.64	1.06	50.64	1.06
1.0	59.61	1.24	59.61	1.24	59.61	1.24	59.61	1.24
1.1	57.78	1.20	57.78	1.20	57.78	1.20	57.78	1.20
1.2	56.52	1.18	56.52	1.18	56.52	1.18	56.52	1.18
1.3	55.79	1.16	55.79	1.16	55.79	1.16	55.79	1.16
1.4	55.41	1.15	55.41	1.15	55.41	1.15	55.41	1.15
1.5	55.25	1.15	55.25	1.15	55.25	1.15	55.25	1.15
1.6	55.34	1.15	55.34	1.15	55.34	1.15	55.34	1.15
1.7	55.59	1.16	55.59	1.16	55.59	1.16	55.59	1.16
1.8	56.02	1.17	56.02	1.17	56.02	1.17	56.02	1.17
1.9	56.51	1.18	56.51	1.18	56.51	1.18	56.51	1.18
2.0	57.11	1.19	57.11	1.19	57.11	1.19	57.11	1.19
2.1	57.83	1.20	57.83	1.20	57.83	1.20	57.83	1.20
2.2	58.42	1.22	58.55	1.22	58.55	1.22	58.55	1.22
2.3	58.82	1.23	59.39	1.24	59.39	1.24	59.39	1.24
2.4	59.19	1.23	60.23	1.25	60.23	1.25	60.23	1.25
2.5	59.61	1.24	61.15	1.27	61.15	1.27	61.15	1.27
2.6	60.01	1.25	62.08	1.29	62.08	1.29	62.08	1.29
2.7	60.46	1.26	63.09	1.31	63.09	1.31	63.09	1.31
2.8	60.89	1.27	64.10	1.34	64.10	1.34	64.10	1.34
2.9	61.38	1.28	65.20	1.36	65.20	1.36	65.20	1.36
3.0	61.84	1.29	66.29	1.38	66.29	1.38	66.29	1.38
3.1	62.31	1.30	67.42	1.40	67.42	1.40	67.42	1.40
3.2	62.75	1.31	68.55	1.43	68.55	1.43	68.55	1.43
3.3	63.23	1.32	69.28	1.44	69.73	1.45	69.73	1.45
3.4	63.68	1.33	69.89	1.46	70.92	1.48	70.92	1.48
3.5	64.17	1.34	70.54	1.47	72.16	1.50	72.16	1.50
3.6	64.64	1.35	71.17	1.48	73.41	1.53	73.41	1.53
3.7	65.11	1.36	71.80	1.50	74.68	1.56	74.68	1.56
3.8	65.57	1.37	72.41	1.51	75.95	1.58	75.95	1.58
3.9	66.06	1.38	73.05	1.52	77.28	1.61	77.28	1.61
4.0	66.53	1.39	73.67	1.53	78.61	1.64	78.61	1.64
4.1	67.09	1.40	74.39	1.55	80.06	1.67	80.06	1.67
4.2	67.65	1.41	75.10	1.56	81.52	1.70	81.52	1.70
4.3	68.20	1.42	75.79	1.58	82.99	1.73	82.99	1.73
4.4	68.75	1.43	76.48	1.59	84.33	1.76	84.47	1.76
4.5	68.79	1.43	76.67	1.60	84.67	1.76	85.47	1.78
4.6	69.33	1.44	77.35	1.61	85.49	1.78	86.98	1.81
4.7	69.86	1.46	78.02	1.63	86.31	1.80	88.50	1.84
4.8	70.38	1.47	78.69	1.64	87.12	1.81	90.03	1.88
4.9	70.89	1.48	79.33	1.65	87.91	1.83	91.56	1.91
5.0	70.97	1.48	79.54	1.66	88.26	1.84	92.67	1.93
5.1	71.47	1.49	80.18	1.67	89.04	1.85	94.23	1.96
Trench width,m	1.1		1.2		1.3		1.4	

Narrow trench load

Wide trench load

DESIGN LOAD CALCULATION FOR DN 500mmSS

Trench cover m	Design load kN/m	Bedding factor	Design load kN/m	Bedding factor	Design load kN/m	Bedding factor	Design load kN/m	Bedding factor
5.2	71.96	1.50	80.80	1.68	89.80	1.87	95.79	2.00
5.3	72.44	1.51	81.42	1.70	90.55	1.89	97.36	2.03
5.4	72.91	1.52	82.01	1.71	91.29	1.90	98.93	2.06
5.5	72.98	1.52	82.21	1.71	91.62	1.91	100.11	2.09
5.6	73.44	1.53	82.80	1.72	92.34	1.92	101.70	2.12
5.7	73.90	1.54	83.37	1.74	93.05	1.94	102.88	2.14
5.8	74.34	1.55	83.94	1.75	93.74	1.95	103.71	2.16
5.9	74.77	1.56	84.50	1.76	94.43	1.97	104.54	2.18
6.0	74.89	1.56	84.73	1.77	94.79	1.97	105.03	2.19
6.1	75.26	1.57	85.22	1.78	95.41	1.99	105.78	2.20
6.2	75.62	1.58	85.70	1.79	96.01	2.00	106.51	2.22
6.3	75.97	1.58	86.16	1.79	96.59	2.01	107.22	2.23
6.4	76.30	1.59	86.61	1.80	97.16	2.02	107.92	2.25
6.5	76.63	1.60	87.04	1.81	97.72	2.04	108.61	2.26
6.6	76.96	1.60	87.49	1.82	98.28	2.05	109.30	2.28
6.7	77.29	1.61	87.93	1.83	98.83	2.06	109.97	2.29
6.8	77.61	1.62	88.35	1.84	99.38	2.07	110.64	2.30
6.9	77.91	1.62	88.77	1.85	99.90	2.08	111.29	2.32
7.0	78.21	1.63	89.17	1.86	100.42	2.09	111.92	2.33
7.1	78.51	1.64	89.57	1.87	100.93	2.10	112.56	2.34
7.2	78.83	1.64	89.99	1.87	101.46	2.11	113.20	2.36
7.3	79.12	1.65	90.39	1.88	101.97	2.12	113.82	2.37
7.4	79.41	1.65	90.77	1.89	102.46	2.13	114.43	2.38
7.5	79.69	1.66	91.15	1.90	102.94	2.14	115.03	2.40
7.6	79.95	1.67	91.51	1.91	103.41	2.15	115.60	2.41
7.7	80.21	1.67	91.86	1.91	103.86	2.16	116.17	2.42
7.8	80.46	1.68	92.21	1.92	104.31	2.17	116.73	2.43
7.9	80.71	1.68	92.54	1.93	104.75	2.18	117.27	2.44
8.0	80.95	1.69	92.87	1.93	105.18	2.19	117.81	2.45
8.1	81.20	1.69	93.21	1.94	105.62	2.20	118.35	2.47
8.2	81.45	1.70	93.55	1.95	106.05	2.21	118.89	2.48
8.3	81.68	1.70	93.87	1.96	106.47	2.22	119.42	2.49
8.4	81.92	1.71	94.20	1.96	106.89	2.23	119.94	2.50
8.5	82.14	1.71	94.50	1.97	107.29	2.24	120.44	2.51
8.6	82.36	1.72	94.80	1.98	107.68	2.24	120.93	2.52
8.7	82.57	1.72	95.10	1.98	108.07	2.25	121.41	2.53
8.8	82.78	1.72	95.38	1.99	108.44	2.26	121.89	2.54
8.9	82.98	1.73	95.66	1.99	108.81	2.27	122.35	2.55
9.0	83.17	1.73	95.93	2.00	109.16	2.27	122.80	2.56
9.1	83.37	1.74	96.21	2.00	109.53	2.28	123.26	2.57
9.2	83.57	1.74	96.49	2.01	109.89	2.29	123.72	2.58
9.3	83.76	1.75	96.75	2.02	110.24	2.30	124.16	2.59
9.4	83.95	1.75	97.02	2.02	110.59	2.30	124.59	2.60
9.5	84.13	1.75	97.27	2.03	110.92	2.31	125.02	2.60
9.6	84.30	1.76	97.51	2.03	111.24	2.32	125.43	2.61
9.7	84.48	1.76	97.76	2.04	111.57	2.32	125.84	2.62
9.8	84.64	1.76	97.99	2.04	111.88	2.33	126.24	2.63
9.9	84.81	1.77	98.22	2.05	112.19	2.34	126.63	2.64
10.0	84.96	1.77	98.44	2.05	112.48	2.34	127.01	2.65
Trench width,m	1.1		1.2		1.3		1.4	

Narrow trench load

Wide trench load